

## Technical Information

No. FO 4961

Edition: 06/02 - subject to change

Substitutes: Edition 06/00

Status: valid

Mercury Short Arc Lamp  
for Microlithography

# HBO<sup>®</sup> 3500 W/PIL SHP

### ■ Product description

The OSRAM HBO<sup>®</sup> 3500 W/PIL SHP is a direct current i-line lamp for microlithography processes within the wafer fabrication for Integrated Circuits. This lamp type emits a very high radiant intensity in the ultraviolet and visible wavelength range and is developed and optimised for being used in ASML equipment (PAS 5500/200B, - 250C). Due to the **SHP**-technology, the lamp is characterized by a very low intensity degradation over lifetime.

### ■ Technical data

Order reference		HBO <sup>®</sup> 3500 W/PIL
Rated lamp wattage	W	3,400
Rated lamp voltage	V	23
Rated lamp current (=)	A	148
Ignition voltage (cold)	kV <sub>s</sub>	max. 20
Radiant intensity (wave length range 365 ± 2,5 nm)	mW/sr	7,370
Electrode gap e	mm	4.5
Lamp length l <sub>1</sub>	mm	max. 360
Lamp length l <sub>2</sub>	mm	320 / max.325
Bulb diameter d	mm	77
LCL a	mm	154
Guaranteed life	h	1500

Base

- Cathode: SFc 32.5-6.7/50
- Anode: SFaX 40-6/50 with cable connection (M10)

### ■ Lamp operation

Maximum permissible base temperature	°C	200
Cooling		Forced base cooling
Burning position		Vertical, anode up

### ■ Safety Instruction

Due to their high luminous efficacy, the UV radiation which they emit and the high pressure within the lamp, HBO<sup>®</sup> lamps may only be operated within enclosed, purpose-built housings. When a lamp breaks, mercury is released. Particular safety regulations should be paid attention (for details please request technical information sheet no. FO 4574).

