

Technical Information

No. FO 5147

Edition: 02/05 - subject to change

Substitutes: 05/03

Status: valid

Mercury Short Arc Lamp
for PCB manufacturing

HBO[®] 5001 W/F

■ Product description

The OSRAM HBO[®] 5001 W/F is a direct current mercury short arc lamp designed for the manufacture of printed circuit boards and semiconductors. This lamp type emits a very high radiant intensity in the ultraviolet and visible wavelength range and is designed with the latest technology for a low intensity degradation over lifetime.

■ Technical data

Order reference	HBO [®]	5001 W/F
Rated lamp wattage	W	5,000
Rated lamp voltage	V	62
Rated lamp current (=)	A	80
Ignition voltage (cold)	kV _S	max.
Radiant intensity (350-450 nm) typical	mW/sr	
Electrode gap e (cold)	mm	7.9
Lamp length (overall) l ₁	mm	max.486
Lamp length l ₂	mm	430
Bulb diameter d	mm	85
LCL a	mm	216
Service life	h	850

Base	<ul style="list-style-type: none">• Cathode: SFXa 38-14/65• Anode: SFa 38-14/65 with cable connection (M10)
------	--

■ Lamp operation

Maximum permissible base temperature	°C	200
Cooling	forced base cooling	
Burning position	vertical, anode (+) down	

■ Safety Instruction

Due to their high luminous efficacy, the UV radiation which they emit and the high pressure within the lamp, HBO[®] lamps must be operated within enclosed, purpose-built housings. When a lamp breaks, mercury is released. Particular safety regulations must be paid attention (for details please request technical information sheet no. FO 4574).

